

# Mobil ATF 3309

## Automatic Transmission Fluid

### Product Description

Mobil ATF 3309 is an exceptionally high performance lubricant that meets original equipment manufacturers' specifications for use in certain slip-controlled lock-up automatic transmissions. Mobil ATF 3309 is recommended for use in transmissions made by Aisin-Warner requiring a fluid approved against Type T-IV, JWS 3309, GM 9986195 and Audi G-052-025-A2. These Aisin-Warner transmissions are used in CERTAIN domestic and foreign vehicles, including Toyota, Lexus, Audi, Saturn, Ford, Volvo, Volkswagen, Saab, Porsche and Mitsubishi.

### Features and Benefits

The unique formulation of Mobil ATF 3309 is designed to provide excellent lubrication of transmissions in specified Aisin-Warner slip-controlled lock-up automatic transmissions. These outstanding performance capabilities translate into significant operational benefits, including:

- Excellent lubricating characteristics for quiet operation and smooth shifting in approved transmissions
- Controlled friction properties for smooth and efficient transmission of power across all normal temperature ranges
- Helps to control transmission shudder and provide excellent vehicle driveability
- Helps to extend transmission life based on excellent wear control
- Long fluid life based on excellent oxidation resistance
- Excellent viscosity stability (high viscosity index) to help assure adequate lubrication without excessive thinning in severe high-temperature service or thickening at low starting temperatures
- Resistance to foaming
- Superb protection against rusting and corrosion
- Compatibility with synthetic rubber seal materials

### Applications

Mobil ATF 3309 is recommended for use in transmissions made by Aisin-Warner requiring fluids approved against JWS 3309 or GM 9986195. It is also recommended for service fill applications where Toyota T-IV, T4, T-III or T3 are called for. Please refer to the owners' manual for proper fluid requirements.



## Specifications & Approvals

MOBIL ATF 3309 has the following specification approvals	Model	Part No. or specification
Audi	TT, A3	G-052-025-A2
Ford	Five Hundred Montego	WSS-M2C924-A
Lexus	Most models	JWS 3309/Type T-IV
Mitsubishi Fuso	FE	2005 & newer vehicles
Porsche	Cayenne S, Cayenne Turbo	JWS 3309/Type T-IV
Saab	9.3, 9.5	All 5-speed automatics
Saturn	Vue, Ion	GM9986195
Toyota	Most models	JW 3309/Type T-IV
Volkswagen	Touareg, Beetle, Cabriolet	*
Volvo	S60, S70, V70, C70, S80, XC90, S40, V40	All 5-speed automatics

\* Check with your dealer or owner's manual

## Typical Properties

Mobil ATF 3309		
Viscosity		
	cSt @ 100°C	7.2
	cSt @ 40°C	35
cP @ -40°C (-40°F)		14,000
Viscosity Index		180
Flash Point, °C		>185
Pour Point, °C		< -45
Density		0.8540
Color		Red

## Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

*The Mobil logotype, the Pegasus design, and Mobil ATF are trademarks of ExxonMobil Corporation, or one of its subsidiaries.*

